WCSS-X Wrap-Around

Cable Support Sleeve

The Mine Cable Services Wrap-Around Cable Support Sleeve is a semi-permanent, strong, streamlined method for providing cable strain relief. Available in a range of sizes, this lightweight and economical strain relief is available to accommodate cable diameter from 0.25" up to 4.95"

Not for use in vertical shaft applications







Product Features and Benefits:

- Semi-permanent, streamlined design will not significantly Increase cable jacket diameter.
- Available for cable diameters ranging from 0.25" to 4.95" diameter (6mm to 126mm diameter).
- Wrap-around sleeve design allows for easy installation on electrical cable already in service.
- Heavy duty nylon strap with hook provides secure anchor point where strain relief is required.
- Anchor hook provides secure tie down point for electrical cable terminations on cable reel for transport.



Proudly Made in Canada





Canada 780-439-1113 Toll Free 1-800-663-2889

> Panamá +507-389-7990

Product Data Sheet

WCSS-X Wrap-Around Cable Support Sleeve

The Mine Cable Services WCSS series of Wrap-Around Cable Support Sleeves provide up to 2,000 lbs. of strain relief for electrical cables when sized and installed correctly. Wrap-Around Cable Support Sleeves are available in range of cable diameters from 0.25" to 4.95" (6mm to 126mm) and can be purchased as single units or in multipacks for ease of warehouse stocking.



roduct Specification	s and Ordering Informa	ation:
Standard Packaging:	Cable Diameter Range: (Inches/mm)	Sleeve Length: (Inches/mm)
1 Each	0.25"-1.20" 6mm-30mm	16" 406mm
1 Each	0.60"-1.80" 15mm-46mm	16" 406mm
1 Each	0.95"-2.70" 24mm-69mm	16" 406mm
1 Each	1.30"-3.60" 33mm-91mm	24" 610mm
1 Each	1.65"-4.95" 42mm-126mm	24" 610mm
	Standard Packaging: 1 Each 1 Each 1 Each 1 Each	Standard Packaging: (Inches/mm) 1 Each 0.25"-1.20" 6mm-30mm 1 Each 0.60"-1.80" 15mm-46mm 1 Each 0.95"-2.70" 24mm-69mm 1 Each 1.30"-3.60" 33mm-91mm 1 Each 1.65"-4.95"

MINE CABLE SERVICES

CORPORATION



Canada 780-439-1113 Toll Free 1-800-663-2889