



# Product Data Sheet

## Rim Drive Cable Reeler



Dual Rim Drive Cable Reeler with variable speed hydraulic power pack.

- This cable reeler is designed with a fully adjustable frame that will accommodate cable reels from 60" to 120" diameter, and 48" to 84" wide.
- Maximum payload is 35,000 lbs (reel and cable combined)
  - Static weight of reeler stand – 1000 lbs
- Rim Drive system is designed to easily adjust to accommodate different sized cable reels
  - Variable speed drive from 1 RPM – 10 RPM



This unit is also our standard rental unit model. Each rental includes the reeler frame, hydraulic power pack, and one certified spindle for your specific requirements.

### Hydraulic Power Pack Specifications:

- 15-25 gallon reservoir
- Internal drip tray on every unit
- Directional control valve with integrate flow control and pressure regulator
- Electric Power Pack includes 7.5-10HP, 208/230V Single phase motor with 3.8 GPM hydraulic pump rated 2000 PSI



• Quick coupling connections from hydraulic unit to rim drive unit for easy set up

Mine Cable Services Corporation 7731 – 16<sup>th</sup> Street NW, Edmonton, Alberta, Canada, T6P 1M1  
Phone. (780) 439-1113 Website: [minecableservices.ca](http://minecableservices.ca) Email: [sales@minecableservices.ca](mailto:sales@minecableservices.ca)